



Firmware for IKS-G6524A Series Release Notes

Version: v5.6	Build: Build_18112620
Release Date: Jan 18, 2019	

Applicable Products

IKS-G6524A Series

Supported Operating Systems

N/A

New Features

N/A

Enhancements

- Web GUI supports web browser Chrome 65.0

Bugs Fixed

- Fix abnormal display of packet counter on the web GUI

Changes

N/A

Notes

N/A



Version: v5.4	Build: Build_17081010
Release Date: Sep 04, 2017	

Applicable Products

IKS-G6524A-20GSFP-4GTXSFP-HV-HV, IKS-G6524A-4GTXSFP-HV-HV, IKS-G6524A-8GSFP-4GTXSFP-HV-HV, IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6524A-4GTXSFP-HV-HV-T, IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- System Notification: Definable Successful/Failed login notifications.
- Password Policy: Password strength can be set.
- Account Lockout Policy: Failure Threshold and Lockout Time can be set.
- Log Management: Full log handling.
- Remote Access Interface Enable/Disable.
- Configuration Encryption with password.
- Support SSL certification import.
- Support MAC Authentication Bypass via RADIUS authentication.
- MAC Address Access Control List or MAC Address filtering.
- Protect against MAC Flooding Attack by MAC address sticky.
- NTP authentication to prevent NTP DDoS attack.
- Login Authentication: Support primary & backup database servers (RADIUS/TACACS+/Local Account).
- Login Authentication via RADIUS Server: Support Challenge Handshake Authentication Protocol (CHAP) Authentication Mechanism.
- RADIUS Authentication: Support EAP-MSCHAPv2 (For Windows7).
- MXview Security View Feature Support* (with MXstudio v2.4).
- Turbo Ring v2, Turbo Chain supports Port Trunking.

Enhancements

- CLI: Support Multiple Sessions (up to six).
- SMTP Supports Transport Layer Security (TLS) Protocol and Removes SSL v2/v3.
- SNMPv3 Traps and Informs.
- Display Issue with Java Applet.
- Fiber Check: Add Threshold Alarm.
- Static Port Lock with IVL Mode.
- When GbE Port Speed is [Auto], MDI/MDIX is [Auto] Fixed.
- Web UI/CLI Command enhancements and modifications.

Bugs Fixed

- When the device received large amounts of BPDU packets on the port that had not enabled the RSTP function, it sometimes caused the device to reboot.
- If there was an '&' character in the column of the switch name, switch location, or switch description, the system info will not show on the 'How Page' information.

Changes

- ate limit add more option on ingress rate

Notes

N/A



Version: v4.2	Build: Build_16112110
Release Date: N/A	

Applicable Products

IKS-G6524A-20GSFP-4GTXSFP-HV-HV, IKS-G6524A-4GTXSFP-HV-HV, IKS-G6524A-8GSFP-4GTXSFP-HV-HV, IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6524A-4GTXSFP-HV-HV-T, IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

N/A

Enhancements

- Encrypted all security passwords and keys in web user interface and the CLI.

Bugs Fixed

N/A

Changes

N/A

Notes

N/A



Version: v4.1	Build: Build_15062312
Release Date: N/A	

Applicable Products

IKS-G6524A-20GSFP-4GTXSFP-HV-HV, IKS-G6524A-4GTXSFP-HV-HV, IKS-G6524A-8GSFP-4GTXSFP-HV-HV, IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6524A-4GTXSFP-HV-HV-T, IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- Added new Multicast Fast Forwarding Mode.

Enhancements

- Increased IGMP Groups to 4096 (original 1000 groups).
- Improved Turbo Chain link status check mechanism at the head port.

Bugs Fixed

- The device rebooted when using CLI commands to back up device configurations to the TFTP server.
- The device rebooted when CLI commands were used to change the SNMP v3 data encryption key and the length of the key is more than 100 characters.

Changes

N/A

Notes

N/A



Version: v4.0	Build: Build_14082811
Release Date: N/A	

Applicable Products

IKS-G6524A-20GSFP-4GTXSFP-HV-HV, IKS-G6524A-4GTXSFP-HV-HV, IKS-G6524A-8GSFP-4GTXSFP-HV-HV, IKS-G6524A-20GSFP-4GTXSFP-HV-HV-T, IKS-G6524A-4GTXSFP-HV-HV-T, IKS-G6524A-8GSFP-4GTXSFP-HV-HV-T

Supported Operating Systems

N/A

New Features

- First release for IKS-G6524A Series.

Enhancements

N/A

Bugs Fixed

N/A

Changes

N/A

Notes

N/A