



## Real TTY drivers for Linux 4.x.x Release Notes

<b>Version: v4.0</b>	<b>Build: Build 19101415</b>
<b>Release Date: Oct 24, 2019</b>	

### Applicable Products

NPort 5100A Series, NPort 5100 Series, NPort P5150A Series, NPort 5200A Series, NPort 5200 Series, NPort 5400 Series, NPort 5600 Series, NPort 5600-DT Series, NPort 5600-DTL Series, NPort Express Series, NPort IA5000A-I/O Series, NPort IAW5000A-I/O Series, NPort S8000 Series, NPort S9450I Series, NPort S9650I Series, NPort W2150A/W2250A Series, NPort IA5000A Series, NPort IA5000 Series, NPort 5000AI-M12 Series, NPort 6100/6200 Series, NPort 6400/6600 Series, CN2510 Series, CN2600 Series, MiiNePort E1 Series, MiiNePort E2 Series, MiiNePort E3 Series, MiiNePort W1 Series, NE-4100 Series

### Supported Operating Systems

Linux Kernel 4.x

### New Features

- Supports the systemd process to load the Real TTY driver on the Linux platform.

### Enhancements

- The connections of the opened TTY ports will not be disconnected and reconnected when adding or removing servers. The related descriptions are also removed in README.txt due to this change.
- Supports virtual machine. The virtual machine ESXi v6.7.0 is tested with guest OS Ubuntu 18.10 x64 and Ubuntu 19.04 x64.
- Supports ARM-based Linux. The Raspbian operating system with Raspberry Pi 2 and 3 are tested.

### Bugs Fixed

- The driver may not set the nonstandard baudrate correctly.
- The driver may have a compiling error with message "malloc.c2401: sysmalloc: Assertion" on the distribution Fedora release 28.
- On the distribution Fedora release 24/26, the service daemon may not start NPort service properly after restarting OS.
- Fixing the driver may not determine the init process correctly when deleting the NPort server.

### Changes

- Divided an independent driver version 4.0 to support only Linux kernel 4.x.

### Notes

N/A



<b>Version: v1.19</b>	<b>Build: N/A</b>
<b>Release Date: Nov 15, 2017</b>	

## Applicable Products

N/A

## Supported Operating Systems

Linux 3.x, Linux 4.x

## New Features

- Supports Raspbian Jessie and later for Raspberry Pi 2/3.
- Added driver background polling feature to eliminate the waiting time when an NPort is not present in Slackware 14.0.

## Enhancements

- Supports kernel 4.13.
- Compiling errors with error message "error: expected expression before '{' token" in specific platforms.
- When using a domain name as the mapping address for NPort, it will be translated every time when Real TTY is opening the port.
- Compiling errors when using secured Real COM mode.
- Shutdown hanging might happen in Red Hat Enterprise Linux 7.2 (3.10.0-123.el7).

## Bugs Fixed

- Real TTY can't start up TTY ports with the domain name mapped after the system is rebooted.
- Kernel panic with error message "unable to handle kernel paging request" on specific platforms.
- Driver doesn't load properly after system reboot on Ubuntu 16.04.
- Driver may cause a kernel crash with the error message "soft lockup" with specific network interface cards.
- The command stty may output an error if there is no loopback connector on NPort in Redundant mode.
- Network reconnection problems when using redundant mode.
- The Real TTY service may not start automatically in Debian 6.0 and later versions.
- There may be communication loss when using IPv6.
- Data can't be read due to abnormal flow control in Linux kernel 3.8 and later.
- When security mode is enabled, the driver may crash if it connects to an offline NPort.
- Port mapping is incorrect after rebooting in Kernel 3.2.48.
- When NPort is offline, the current serial parameters are not saved for reconnection.
- While executing mxsetsec, the configuration of the driver will be cleared.
- When opening node /dev/ttyr10, port 16 should be opened, but port 10 is opened instead.
- The driver reference count becomes negative after a port open fails.

## Changes

- No longer supports kernel 2.x.
- Log file increasing without limit causes a file system crash.

## Notes

N/A