

LM-7000H 模組系列

適用於 PT-G7728/G7828 系列與 MDS-G4012/20/28 系列的乙太網路與 PoE+ 模組



特色與優點

- -40°C 至 85°C 寬範圍操作溫度
- 符合 IEC 61850-3 及 IEEE 1613 規範
- 符合 IEC 62439-3 第 4 條 (PRP) 與第 5 條 (HSR)
- 可熱插拔

認證



簡介

LM-7000H 模組系列專為 PT-G7728/G7828 系列與 MDS-G4012/G4020/G4028 系列 IEC 61850-3 乙太網路交換器所設計。這些模組為受支援的交換器提供額外的彈性，每個模組可讓您新增 4 個 Gigabit 乙太網路或 PoE 連接埠，或 2 個 Gigabit PRP/HSR 連接埠。

規格

Ethernet Interface

PoE Ports (100/1000BaseT(X), RJ45 connector)	LM-7000H-4GPoE: 4
10/100BaseT(X) Ports (RJ45 connector)	LM-7000H-4TX: 4
PoE Ports (10/100BaseT(X), RJ45 connector)	LM-7000H-4PoE: 4
100/1000BaseSFP Slots	LM-7000H-4GSFP: 4
10/100/1000BaseT(X) Ports (RJ45 connector)	LM-7000H-4GTX: 4
Combo Ports (100/1000BaseT(X) PRP/HSR or 100/1000BaseSFP PRP/HSR)	LM-7000H-2GPHR: 2 (for PT-G7728 Series and MDS-G4012/G4020/G4028 (non-L3 only) Series)

Power Parameters

Power Consumption	LM-7000H-4GTX: 3.63 W (max.) LM-7000H-4GPoE: 3.8 W (max.) LM-7000H-4GSFP: 4.8 W (max.) LM-7000H-4TX: 1.85 W (max.) LM-7000H-4PoE: 1.85 W (max.) LM-7000H-2GPHR: 8.1 W (max.)
-------------------	---

Physical Characteristics

Weight	LM-7000H-4GSFP: 0.3 kg (0.66 lb) LM-7000H-4GTX: 0.24 kg (0.53 lb) LM-7000H-4GPoE: 0.31 kg (0.69 lb) LM-7000H-4TX: 0.24 kg (0.53 lb) LM-7000H-4PoE: 0.31 kg (0.69 lb) LM-7000H-2GPHR: 0.31 kg (0.69 lb)
--------	---

MTBF

Time	LM-7000H-4GPoE: 1,280,518 hrs LM-7000H-4GSFP: 2,475,903 hrs LM-7000H-4GTX: 2,641,729 hrs LM-7000H-4PoE: 1,280,220 hrs LM-7000H-4TX: 2,640,462 hrs LM-7000H-2GPHR: 1,832,962 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/tw/warranty

訂購資訊

Model Name	10/100/ 1000BaseT(X) Ports	10/100BaseT(X) Ports	100/ 1000BaseSFP Slots	100/ 1000BaseT(X) PoE Ports	10/100BaseT(X) PoE Ports	Combo Ports (10/100/ 1000BaseT(X) PRP/HSR or 100/ 1000BaseSFP PRP/HSR)	Operating Temp.
LM-7000H-4GTX	4	-	-	-	-	-	-45 to 85°C
LM-7000H-4TX	-	4	-	-	-	-	-45 to 85°C
LM-7000H-4GPoE	-	-	-	4	-	-	-45 to 85°C
LM-7000H-4PoE	-	-	-	-	4	-	-45 to 85°C
LM-7000H-4GSFP	-	-	4	-	-	-	-45 to 85°C
LM-7000H-2GPHR	-	-	-	-	-	2	-45 to 75°C

配件 (選購)

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode with LC connector for 4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature

SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXLC	SFP module with 1 1000BaseEZXC port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXLC-120	SFP module with 1 1000BaseEZXC port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXC	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, 0 to 60°C operating temperature
SFP-1GLSXC-T	SFP module with 1 1000BaseLSX port with LC connector for 1km/2km transmission, -40 to 85°C operating temperature
SFP-1GLXC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXC	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, 0 to 60°C operating temperature
SFP-1GSXC-T	SFP module with 1 1000BaseSX port with LC connector for 300m/550m transmission, -40 to 85°C operating temperature
SFP-1GZXC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZXC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature

© Moxa Inc. 版權所有.2025 年 9 月 18 日更新。

未經 Moxa Inc. 明確書面許可，不得以任何方式複製或使用本文件及其任何部分。產品規格如有變更，恕不另行通知。請至本公司官網了解最新的產品資訊。