

RM-G4000モジュールシリーズ

RKS-G4028シリーズラックマウントイーサネットスイッチ用のファストイーサネットおよびギガビットモジュール

機能と特長

- 動作温度範囲-40~75°C
- IEC 61850-3およびIEEE 1613準拠



認証



製品紹介

RM-G4000モジュールシリーズには、RKS-G4000シリーズラックマウントイーサネットスイッチ用のギガビットおよび高速イーサネットモジュールが含まれています。各RM-G4000シリーズモジュールは、TX、MSC、SSC、MSTメディアタイプなど、さまざまなインターフェースタイプを備えた最大8つのポートをサポートします。さらに、RM-G4000-8GPoEおよびRM-G4000-8PoEモジュールは、RKS-G4000シリーズPoEモデルに大容量PoE機能を提供します。IEEE 1588インターフェースモジュールは、ハードウェアベースのPTP機能を提供し、ネットワーク全体で正確な時間同期を実現します。

仕様

Ethernet Interface

10/100BaseT(X) Ports (RJ45 connector)	RM-G4000-8TX: 8 RM-G4000-2MSC4TX: 4 RM-G4000-2MST4TX: 4 RM-G4000-2SSC4TX: 4 RM-G4000-4MSC2TX: 2 RM-G4000-4MST2TX: 2 RM-G4000-4SSC2TX: 2
10/100/1000BaseT(X) Ports (RJ45 connector)	RM-G4000-8GTX: 8
100/1000BaseSFP Slots	RM-G4000-8GSFP: 8
100BaseSFP Slots	RM-G4000-8SFP: 8
100BaseFX Ports (multi-mode SC connector)	RM-G4000-6MSC: 6 RM-G4000-2MSC4TX: 2 RM-G4000-4MSC2TX: 4
100BaseFX Ports (multi-mode ST connector)	RM-G4000-6MST: 6 RM-G4000-2MST4TX: 2 RM-G4000-4MST2TX: 4
100BaseFX Ports (single-mode ST connector)	RM-G4000-6SSC: 6 RM-G4000-2SSC4TX: 2 RM-G4000-4SSC2TX: 4
PoE Ports (10/100/1000BaseT(X), RJ45 connector)	RM-G4000-8GPoE: 8

PoE Ports (10/100BaseT(X), RJ45 connector)	RM-G4000-8PoE: 8			
Optical Fiber			100BaseFX	
			Multi-Mode	
			Single-Mode	
	Fiber Cable Type	OM1	50/125 μ m	G.652
			800 MHz x km	
	Typical Distance	4 km	5 km	40 km
	Wavelength	Typical (nm)	1300	
		TX Range (nm)	1260 to 1360	
		RX Range (nm)	1100 to 1600	
	Optical Power	TX Range (dBm)	-10 to -20	
		RX Range (dBm)	-3 to -32	
		Link Budget (dB)	12	
		Dispersion Penalty (dB)	3	
	<p>Note: When connecting a single-mode fiber transceiver, we recommend using an attenuator to prevent damage caused by excessive optical power.</p> <p>Note: Compute the “typical distance” of a specific fiber transceiver as follows: Link budget (dB) > dispersion penalty (dB) + total link loss (dB).</p>			

Power Parameters

Power Consumption (Max.)	RM-G4000-8TX: 4.22 W RM-G4000-8GTX: 4.22 W RM-G4000-8PoE: 4.75 W RM-G4000-8GPoE: 4.75 W RM-G4000-8SFP: 6.91 W RM-G4000-8GSFP: 6.91 W RM-G4000-6MSC: 4.61 W RM-G4000-6MST: 4.61 W RM-G4000-6SSC: 5.47 W RM-G4000-2MSC4TX: 2.88 W RM-G4000-2MST4TX: 2.88 W RM-G4000-2SSC4TX: 3.17 W RM-G4000-4MSC2TX: 3.74 W RM-G4000-4MST2TX: 3.74 W RM-G4000-4SSC2TX: 4.03 W
--------------------------	--

Physical Characteristics

Weight	RM-G4000-8TX: 300 g (0.66 lb) RM-G4000-8GTX: 300 g (0.66 lb) RM-G4000-8PoE: 500 g (1.10 lb) RM-G4000-8GPoE: 500 g (1.10 lb) RM-G4000-8SFP: 400 g (0.88 lb) RM-G4000-8GSFP: 400 g (0.88 lb) RM-G4000-6MSC: 400 g (0.88 lb) RM-G4000-6MST: 400 g (0.88 lb) RM-G4000-6SSC: 400 g (0.88 lb) RM-G4000-2MSC4TX: 400 g (0.88 lb) RM-G4000-2MST4TX: 400 g (0.88 lb) RM-G4000-2SSC4TX: 400 g (0.88 lb) RM-G4000-4MSC2TX: 400 g (0.88 lb) RM-G4000-4MST2TX: 400 g (0.88 lb) RM-G4000-4SSC2TX: 400 g (0.88 lb)
--------	---

MTBF

Time	RM-G4000-8TX: 12,132,675 hrs RM-G4000-8GTX: 12,132,675 hrs RM-G4000-8PoE: 2,063,404 hrs RM-G4000-8GPoE: 2,063,404 hrs RM-G4000-8SFP: 3,005,803 hrs RM-G4000-8GSFP: 3,005,803 hrs RM-G4000-6MSC: 2,183,161 hrs RM-G4000-6MST: 2,183,161 hrs RM-G4000-6SSC: 2,183,161 hrs RM-G4000-2MSC4TX: 2,891,502 hrs RM-G4000-2MST4TX: 2,891,502 hrs RM-G4000-2SSC4TX: 2,891,502 hrs RM-G4000-4MSC2TX: 2,469,891 hrs RM-G4000-4MST2TX: 2,469,891 hrs RM-G4000-4SSC2TX: 2,469,891 hrs
Standards	Telcordia (Bellcore), GB

Warranty

Warranty Period	5 years
Details	See www.moxa.com/jp/warranty

Package Contents

Device	1 x RM-G4000 Series module
Documentation	1 x warranty card

注文情報

Model Name	10/100/ 1000BaseT(X) Ports	10/100BaseT(X) Ports	100/ 1000BaseSFP Ports	100BaseSFP Ports	100BaseFX Ports Multi- mode, SC Connector	100BaseFX Port Multi-mode, ST Connector	100BaseFX Port Single-mode, SC Connector
RM-G4000-8GTX	8	-	-	-	-	-	-
RM-G4000-8TX	-	8	-	-	-	-	-
RM-G4000-8GSFP	-	-	8	-	-	-	-
RM-G4000-8SFP	-	-	-	8	-	-	-
RM-G4000-6MSC	-	-	-	-	6	-	-
RM-G4000-6MST	-	-	-	-	-	6	-
RM-G4000-6SSC	-	-	-	-	-	-	6
RM-G4000-4MSC2TX	-	2	-	-	4	-	-
RM-G4000-4MST2TX	-	2	-	-	-	4	-
RM-G4000-4SSC2TX	-	2	-	-	-	-	4
RM-G4000-2MSC4TX	-	4	-	-	2	-	-
RM-G4000-2MST4TX	-	4	-	-	-	2	-
RM-G4000-2SSC4TX	-	4	-	-	-	-	2
RM-G4000-8GPoE	8 (IEEE 802.3bt PoE)	-	-	-	-	-	-
RM-G4000-8PoE	-	8 (IEEE 802.3bt PoE)	-	-	-	-	-

アクセサリ (別売)

SFP Modules

SFP-1FELLC-T	SFP module with 1 100Base single-mode with LC connector for 80 km transmission, -40 to 85°C operating temperature
SFP-1FEMLC-T	SFP module with 1 100Base multi-mode with LC connector for 4 km transmission, -40 to 85°C operating temperature
SFP-1FESLC-T	SFP module with 1 100Base single-mode with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1G10ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G10ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G10BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G10BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 10 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G20ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G20ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G20BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G20BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 20 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1G40ALC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, 0 to 60°C operating temperature
SFP-1G40ALC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1310 nm, RX 1550 nm, -40 to 85°C operating temperature
SFP-1G40BLC	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, 0 to 60°C operating temperature
SFP-1G40BLC-T	WDM-type (BiDi) SFP module with 1 1000BaseSFP port with LC connector for 40 km transmission; TX 1550 nm, RX 1310 nm, -40 to 85°C operating temperature
SFP-1GEZXC	SFP module with 1 1000BaseEZXC port with LC connector for 110 km transmission, 0 to 60°C operating temperature
SFP-1GEZXC-120	SFP module with 1 1000BaseEZXC port with LC connector for 120 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, 0 to 60°C operating temperature
SFP-1GLHLC-T	SFP module with 1 1000BaseLH port with LC connector for 30 km transmission, -40 to 85°C operating temperature
SFP-1GLHXLC	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, 0 to 60°C operating temperature
SFP-1GLHXLC-T	SFP module with 1 1000BaseLHX port with LC connector for 40 km transmission, -40 to 85°C operating temperature
SFP-1GLSXLC	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, 0 to 60°C operating temperature
SFP-1GLSXLC-T	SFP module with 1 1000BaseLSX port with LC connector for 500 m transmission, -40 to 85°C operating temperature
SFP-1GLXLC	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, 0 to 60°C operating temperature
SFP-1GLXLC-T	SFP module with 1 1000BaseLX port with LC connector for 10 km transmission, -40 to 85°C operating temperature
SFP-1GSXLC	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, 0 to 60°C operating temperature

SFP-1GSXLC-T	SFP module with 1 1000BaseSX port with LC connector for 300/550 m transmission, -40 to 85°C operating temperature
SFP-1GZLC	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, 0 to 60°C operating temperature
SFP-1GZLC-T	SFP module with 1 1000BaseZX port with LC connector for 80 km transmission, -40 to 85°C operating temperature

© Moxa Inc. All rights reserved.2023年1月9日更新。

Moxa Inc.の明白な許可を面で取得しない限り、本書およびその一部の複製や使用はいかなる方法やいかなる場合でも許可されません。製品の仕様は予告なく変更されることがあります。最新の製品情報については当社のWebサイトをご覧ください。