

Power Cords

Power cords for different regions

Features and Benefits

- Provides different plug types for desktop type power adapters



Introduction

The power cords described in this datasheet provide the different plug types used in different regions or countries for desktop type power adapters or Moxa products with AC power inputs.

Appearance

CBL-PJ21NOPEN-BK-30



CBL-PJTB-10



PWC-C15EU-3B-183



PWC-C15US-3B-183



Specifications

Power Parameters

Input Plug Type	PWC-AU models: Australia plug type PWC-CN models: China plug type PWC-EU models: Europe plug type PWC-JP models: Japan plug type PWC-UK models: United Kingdom plug type PWC-US models: United States plug type
Input Voltage	JP/US models: 125 VAC AU/CN/EU/UK models: 250 VAC
Max. Current	PWC-C15EU-3B-183: 10 A PWC-C15US-3B-183: 15 A PWC-C13AU-3B-183: 10 A PWC-C13CN-3B-183: 10 A PWC-C13EU-3B-183: 10 A PWC-C13JP-3B-183: 7 A PWC-C13UK-3B-183: 10 A PWC-C13US-3B-183: 10 A PWC-C7AU-2B-183: 2.5 A PWC-C7CN-2B-183: 2.5 A PWC-C7EU-2B-183: 2.5 A PWC-C7JP-2B-183: 7 A PWC-C7UK-2B-183: 2.5 A PWC-C7US-2B-183: 10 A

Physical Characteristics

Thickness	PWC-C15EU-3B-183: 7.0±0.2 mm (0.28±0.01 in) PWC-C15US-3B-183: 9.3±0.2 mm (0.37±0.01 in) PWC-C13AU-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13CN-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13EU-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13JP-3B-183: 7.0±0.2 mm (0.28±0.01 in) PWC-C13UK-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13US-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C7CN-2B-183: 5.6±0.2 mm (0.22±0.01 in) PWC-C7AU-2B-183: 5.6±0.2 mm (0.22±0.01 in) PWC-C7UK-2B-183: 5.6±0.2 mm (0.22±0.01 in) PWC-C7EU-2B-183: 5.6±0.2 mm (0.22±0.01 in) PWC-C7JP-2B-183: 6.6±0.2 mm (0.26±0.01 in) PWC-C7US-2B-183: 6.3±0.2 mm (0.25±0.01 in)
Length	PWC-C13 models: 1830±30 mm (72.05±1.18 in) PWC-C15 models: 1830 mm (72 in) PWC-C7 models: 1830±200 mm (72.05±7.87 in)
Cable Length	CBL-PJ21NOPEN-BK-30 w/Nut: 300 ± 20 mm (11.81 ± 0.79 in) CBL-PJTB-10: 100 ± 20 mm (3.94 ± 0.79 in)

Ordering Information

Model Name	Barrel-plug Type	Input-plug Type	Input Voltage
PWC-C15EU-3B-183	–	EU	250 VAC
PWC-C15US-3B-183	–	US	125 VAC
PWC-C13AU-3B-183	–	AU	250 VAC
PWC-C13CN-3B-183	–	CN	250 VAC
PWC-C13EU-3B-183	–	EU	250 VAC
PWC-C13JP-3B-183	–	JP	125 VAC
PWC-C13UK-3B-183	–	UK	250 VAC
PWC-C13US-3B-183	–	US	125 VAC
PWC-C7AU-2B-183	–	AU	250 VAC

Model Name	Barrel-plug Type	Input-plug Type	Input Voltage
PWC-C7CN-2B-183	–	CN	250 VAC
PWC-C7EU-2B-183	–	EU	250 VAC
PWC-C7JP-2B-183	–	JP	125 VAC
PWC-C7UK-2B-183	–	UK	250 VAC
PWC-C7US-2B-183	–	US	125 VAC
CBL-PJ21NOPEN-BK-30	Locking	–	–
CBL-PJTB-10	Non-locking	–	–

© Moxa Inc. All rights reserved. Updated Jun 09, 2025.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.